

VFR (2,0 mm)

Vulkaniseeritud kiust rõngastihend, paksus 2 mm

HANSA FLEX

Omadused

| | |
|----------|----------------------|
| Tavaline | DIN 7603-A |
| Materjal | Vulkaniseeritud kiud |



Artikkel

| Märgistus | d1 (mm) | d2 (mm) | S (mm) |
|----------------|------------|------------|-----------|
| VFR 6.2-17.5-2 | 6,20 | 17,50 | 2,00 |
| VFR 24-30-2 | 24,00 | 30,00 | 2,00 |
| VFR 26-32-2 | 26,00 | 32,00 | 2,00 |
| VFR 27-32-2 | 27,00 | 32,00 | 2,00 |
| VFR 28-34-2 | 28,00 | 34,00 | 2,00 |
| VFR 30-36-2 | 30,00 | 36,00 | 2,00 |
| VFR 32-38-2 | 32,00 | 38,00 | 2,00 |
| VFR 33-39-2 | 33,00 | 39,00 | 2,00 |
| VFR 35-41-2 | 35,00 | 41,00 | 2,00 |
| VFR 36-42-2 | 36,00 | 42,00 | 2,00 |
| VFR 40-47-2 | 40,00 | 47,00 | 2,00 |
| VFR 42-49-2 | 42,00 | 49,00 | 2,00 |
| VFR 45-52-2 | 45,00 | 52,00 | 2,00 |
| VFR 48-55-2 | 48,00 | 55,00 | 2,00 |