

PRT S DN

Perrot-ühendus, isane detail voolikühendusega

HANSA FLEX

Omadused

Ühendus 1 Ühendus, isane detail

Materjal Teras

Pinnatöötlus must



Artikkel

Märgistus	Töörõhk (bar)	Ühendusmäär (mm)	Vooliku-ID jaoks (mm)
PRT S 50 DN 50	12,0	50,0	50
PRT S 70 DN 63	12,0	70,0	63
PRT S 70 DN 70	12,0	70,0	70
PRT S 70 DN 75	12,0	70,0	75
PRT S 89 DN 75	12,0	89,0	75
PRT S 89 DN 80	12,0	89,0	80
PRT S 89 DN 89	12,0	89,0	89
PRT S 108 DN 75	12,0	108,0	75
PRT S 108 DN 90	12,0	108,0	90
PRT S 108 DN 102	12,0	108,0	102
PRT S 108 DN 110	12,0	108,0	110
PRT S 108 DN 152	12,0	108,0	152
PRT S 108 DN 127	12,0	108,0	127
PRT S 133 DN 50	12,0	133,0	50
PRT S 133 DN 76	12,0	133,0	76
PRT S 133 DN 102	12,0	133,0	102
PRT S 133 DN 110	12,0	133,0	110
PRT S 133 DN 127	12,0	133,0	127
PRT S 133 DN 133	12,0	133,0	133
PRT S 133 DN 152	12,0	133,0	152
PRT S 159 DN 50	12,0	159,0	50
PRT S 159 DN 76	12,0	159,0	76
PRT S 159 DN 102	12,0	159,0	102
PRT S 159 DN 127	12,0	159,0	127
PRT S 159 DN 133	12,0	159,0	133
PRT S 159 DN 152	12,0	159,0	152
PRT S 159 DN 159	12,0	159,0	159
PRT S 216 DN 200	12,0	216,0	200