

PRT S HR

Perrot-ühendus, isane detail, väliskeere

HANSA FLEX

Omadused

Ühendus 1	Ühendus, isane detail
Ühendus 2	BSP-väliskeere, silindriline
Materjal	Teras
Pinnatöötlus	tules tsingitud



Artikkel

Märgistus	Töörõhk (bar)	Ühendusmäär (mm)	G1
PRT S 50 HR 1.1/2	25,0	50,0	G 1.1/2" -11
PRT S 50 HR 2	25,0	50,0	G 2" -11
PRT S 70 HR 2	25,0	70,0	G 2" -11
PRT S 70 HR 2.1/2	25,0	70,0	G 2.1/2" -11
PRT S 70 HR 3	25,0	70,0	G 3" -11
PRT S 89 HR 2.1/2	25,0	89,0	G 2.1/2" -11
PRT S 89 HR 3	25,0	89,0	G 3" -11
PRT S 108 HR 2.1/2	25,0	108,0	G 2.1/2" -11
PRT S 108 HR 3	25,0	108,0	G 3" -11
PRT S 108 HR 4	25,0	108,0	G 4" -11
PRT S 133 HR 2.1/2	25,0	133,0	G 2.1/2" -11
PRT S 133 HR 4	25,0	133,0	G 4" -11
PRT S 133 HR 5	25,0	133,0	G 5" -11
PRT S 159 HR 2.1/2	25,0	159,0	G 2.1/2" -11
PRT S 159 HR 4	25,0	159,0	G 4" -11
PRT S 159 HR 6	25,0	159,0	G 6" -11