

## Omadused

<b>Ühendus 1</b>	Jäik äärik surveastmega PN16
<b>Ehitustüüp</b>	Sirge
<b>Tihenditüüp 1</b>	Lametihend
<b>Rakendusvaldkond</b>	Tööstus
<b>Tavaline</b>	DIN EN 1092-1
<b>Materjal</b>	Roostevaba teras



## Artikkel

Märgistus	DN*	Suurus	Toll	Ø D (mm)	K (mm)	Ø d2 (mm)	N (mm)
TUE G 25 FF PN16 VA	25	16	1"	115,0	85	14	4
TUE G 32 FF PN16 VA	32	20	1.1/4"	140,0	100	18	4
TUE G 38 FF PN16 VA	40	24	1.1/2"	150,0	110	18	4
TUE G 50 FF PN16 VA	50	32	2"	165,0	125	18	4
TUE G 63 FF PN16 VA	63	40	2.1/2"	-	-	-	-
TUE G 75 FF PN16 VA	75	50	3"	200,0	160	18	8
TUE G 102 FF PN16 VA	100	64	4"	220,0	180	18	8

N = avade arv

## Lisatarvikud

<b>KS AL</b>	Klambriarmatuur, alumiinium
<b>KS FIX AL</b>	Tihvtidega kinnitamiseks mõeldud klemmarmatuur, alumiiniumist

## Täiendavad elemendid

<b>FD C4400</b>	Lametihend
-----------------	------------