

# K-PUR-BREMSSPIRALE

PUR brake coil with connection

**HANSA FLEX**

## Omadused

<b>Ühendus 1 + 2</b>	M-keere välis, silindriline
<b>Tavaline</b>	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
<b>Luba</b>	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
<b>Temperatuur min.</b>	-40 °C
<b>Temperatuur max.</b>	90 °C
<b>Materjal</b>	PUR



## Lisateave

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

## Artikkel

Märgistus	G1 + G2	Sisemine-Ø (mm)	Välise-Ø (mm)	Seina tugevus (mm)	Pikkus (m)	Värv
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	must
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	kollane
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	punane
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	must
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	kollane
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	punane