

K-KFMM H MBAR

Capsule-type pressure gauges, connection on rear

HANSA FLEX

Omadused	
Tüüp	611.10 (Ø 63), 612.20 (Ø 100)
Rakendamine	Capsule-type pressure gauge
Rakendus	For gaseous, dry, non-corrosive media
Kvaliteediklass	1,6
Aine temperatuur	max. +100 °C; max. +80 °C (at type Ø 100 mm, rear connector excentric)
Keskonnatemperatuur	-20 °C kuni +60 °C
Korpus	Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)
Mõõtelemendi ja osutimehhanismi materjal	Vasesulam
Klaas	Plexiglass (Ø 63 mm), flat instrument glass (Ø 100 mm)



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

With zero correction

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 06 97	0 - 40 mbar	63,0	G 1/4"
K- 07 20 06 98	0 - 60 mbar	63,0	G 1/4"
K- 07 20 06 99	0 - 100 mbar	63,0	G 1/4"
K- 07 20 07 00	0 - 160 mbar	63,0	G 1/4"
K- 07 20 07 01	0 - 250 mbar	63,0	G 1/4"
K- 07 20 07 02	0 - 400 mbar	63,0	G 1/4"
K- 07 20 01 25	0 - 25 mbar	100,0	G 1/2"
K- 07 20 01 26	0 - 40 mbar	100,0	G 1/2"
K- 07 20 01 27	0 - 60 mbar	100,0	G 1/2"
K- 07 20 01 28	0 - 100 mbar	100,0	G 1/2"
K- 07 20 01 29	0 - 160 mbar	100,0	G 1/2"
K- 07 20 01 30	0 - 250 mbar	100,0	G 1/2"
K- 07 20 01 31	0 - 400 mbar	100,0	G 1/2"