

K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

HANSA FLEX

Omadused

Tüüp	422.12 (robust), 432.50 (chemical)
Rakendamine	Diaphragm pressure gauge in robust design or for chemical applications
Rakendus	at chemical applications in aggressive environments for gaseous or liquid media,
Kvaliteediklass	1,6
Aine temperatuur	max. +100 °C
Keskonnatemperatuur	-20 °C kuni +60 °C
Mõõteääriku Ø	100 mm
Korpus, rõngas	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
Mõõteelement	CrNi steel
Klaas	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
Osimehanism	Copper alloy (robust type), CrNi steel (type for chemical applications)



Vihje

Lisaandmed saate soovi korral.

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 10 99	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 00	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 11 01	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 11 02	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 11 03	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 11 04	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 11 05	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 11 06	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 11 07	0 - 25.0 bar	100,0	G 1/2"