

K-MANO ROB U

Robust pressure gauges, connection radial on bottom

HANSA FLEX

Omadused

Tüüp	212.20
Rakendamine	Robust Bourdon-tube pressure gauge
Rakendus	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kvaliteediklass	1,0
Aine temperatuur	max. +80 °C
Keskonnatemperatuur	-40 °C to +60 °C
Korpus	CrNi steel
Mõõteelement	Copper alloy (≤ 100 bar), CrNi steel (> 100 bar)
Klaas	Flat instrument glass
Osutimehhanism	Copper alloy



Vihje

Lisaandmed saate soovi korral.

Lisateave

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 01 44	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 45	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 46	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 47	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 48	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 49	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 01 50	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 01 51	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 52	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 53	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 54	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 55	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 56	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 57	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 58	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 59	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 60	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 61	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 62	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 63	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 64	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 65	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 01 66	0 - 1000.0 bar	100,0	G 1/2"
K- 07 20 03 24	-1 / 0.0 bar	160,0	G 1/2"
K- 07 20 03 25	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 26	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 27	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 28	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 29	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 30	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 31	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 32	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 33	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 34	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 35	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 36	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 37	0 - 160.0 bar	160,0	G 1/2"



Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.

05.06.2026

HANSA-FLEX AG

www.hansa-flex.com

K-MANO ROB U

Robust pressure gauges, connection radial on bottom

HANSA FLEX

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 03 38	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 39	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 40	0 - 600.0 bar	160,0	G 1/2"