
K-MANO ABSPH MUF ZAPF

Pressure gauge stopcocks, female - male

Omadused

Rakendus	For all pressure gauges with a flat gasket acc. to DIN 16258
Rõhuvahemik	Max. 16 bar, depending on the variantPressure gauge valves should be used for higher pressures
Temperatuur	Max. +50 °C
Korpus	Brass with a bare metal surface or stainless steel 1.4571
Käepide	Plastic
Kontrolläärik	-



Vihje

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Lisaandmed saate soovi korral.

Kirjeldus

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Lisateave

Further measuring ranges on request
Version for panel mounting available on request. Version with max. pointer available on request

Artikkel

Märgistus	Keere	PN (bar)	SW (mm)	Materjal
K- 07 20 10 94	G 1/4	6	17	Messing
K- 07 20 10 95	G 3/8	16	22	Messing
K- 07 20 10 97	G 1/2	25	27	Messing
K- 07 20 10 96	G 1/2	25	27	Stainless steel
K- 07 20 10 98	G 1/2	25	27	Messing

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.