

K-RMM H STAHL

Standard pressure gauges (sheet steel housing / connection on rear, central)

HANSA FLEX

Omadused	
Tüüp	111.12
Rakendamine	Bourdon-tube pressure gauge in standard design
Rakendus	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kvaliteediklass	1.6 (Art. No. K-07200599, K-07200600: 2.5)
Aine temperatuur	max +60 °C
Keskonnatemperatuur	-20 °C kuni +60 °C
Korpus	Sheet steel
Mõõteelemendi ja osutimehhanismi materjal	Vasesulam
Klaas	Transparent plastic



Vihje

Lisaandmed saate soovi korral.

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 04 74	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 75	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 76	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 77	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 78	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 79	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 80	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 81	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 82	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 89	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 90	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 91	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 92	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 93	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 94	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 95	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 96	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 97	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 98	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 99	0 - 60.0 bar	50,0	G 1/4
K- 07 20 06 00	0 - 100.0 bar	50,0	G 1/4
K- 07 20 11 84	0 - 1.0 bar	40,0	G 1/8