

K-RMM U STAHL

Standard pressure gauges (sheet steel housing / connection radial on bottom)

HANSA FLEX

Omadused	
Tüüp	111.10
Rakendamine	Bourdon-tube pressure gauge in standard design
Rakendus	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kvaliteediklass	1.6 (Art. No. K-07200581: 2.5)
Aine temperatuur	max +60 °C
Keskonnatemperatuur	-20 °C kuni +60 °C
Korpus	Sheet steel
Mõõteelementi ja osutimehhanismi materjal	Vasesulam
Klaas	Transparent plastic



Vihje

Lisaandmed saate soovi korral.

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 04 65	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 66	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 67	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 68	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 69	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 70	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 71	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 72	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 73	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 76	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 77	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 78	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 79	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 80	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 81	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 82	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 83	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 84	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 85	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 86	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 87	0 - 100.0 bar	50,0	G 1/4
K- 07 20 05 88	0 - 160.0 bar	50,0	G 1/4