

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

Omadused

Töötemperatuur	-60 °C to +100 °C (PA 12)
Omadused	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Toru pikkus	3 m
Pakkeühik	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Materjal	Polyamid PA 12, hard (according to DIN 73378)



Vihje

Operating pressure with 2.5 x overpressure safety!

Lisaandmed saate soovi korral.

Kirjeldus

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikkel

Märgistus	Toru välimine Ø (mm)	Toru sise-Ø (mm)	max töö rõhk 20 °C juures (bar)	Värv
K- 07 10 04 57	12	9	38	sinine
K- 07 10 04 59	12	9	38	must
K- 07 10 04 61	15	12	25	sinine
K- 07 10 04 63	15	12	25	must
K- 07 10 04 65	18	14	28	sinine
K- 07 10 04 67	18	14	28	must
K- 07 10 04 69	22	18	22	sinine
K- 07 10 04 71	22	18	22	must
K- 07 10 04 73	28	23	20	sinine
K- 07 10 04 75	28	23	20	must