

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Omadused

Töötemperatuur	-60 °C to +100 °C (PA 12)
Omadused	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Toru pikkus	3 m
Pakkeühik	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materjal	Polyamid PA 12, hard (according to DIN 73378)



Vihje

Operating pressure with 2.5 x overpressure safety!

Lisaandmed saate soovi korral.

Kirjeldus

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikkel

Märgistus	Toru välimine Ø (mm)	Toru sise-Ø (mm)	max töö rõhk 20 °C juures (bar)	Värv
K- 07 10 04 56	12	9	38	sinine
K- 07 10 04 58	12	9	38	must
K- 07 10 04 60	15	12	25	sinine
K- 07 10 04 62	15	12	25	must
K- 07 10 04 64	18	14	28	sinine
K- 07 10 04 66	18	14	28	must
K- 07 10 04 68	22	18	22	sinine
K- 07 10 04 70	22	18	22	must
K- 07 10 04 72	28	23	20	sinine
K- 07 10 04 74	28	23	20	must