

# K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

**HANSA FLEX**

## Omadused

<b>Töötemperatuur</b>	-60 °C to +100 °C (PA 12)
<b>Omadused</b>	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
<b>Toru pikkus</b>	3 m
<b>Pakkeühik</b>	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
<b>Materjal</b>	Polyamid PA 12, hard (according to DIN 73378)



## Vihje

Operating pressure with 2.5 x overpressure safety!

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Artikkel

Märgistus	Toru välimine Ø (mm)	Toru sise-Ø (mm)	max töö rõhk 20 °C juures (bar)	Värv
K- 07 10 04 56	12	9	38	sinine
K- 07 10 04 58	12	9	38	must
K- 07 10 04 60	15	12	25	sinine
K- 07 10 04 62	15	12	25	must
K- 07 10 04 64	18	14	28	sinine
K- 07 10 04 66	18	14	28	must
K- 07 10 04 68	22	18	22	sinine
K- 07 10 04 70	22	18	22	must
K- 07 10 04 72	28	23	20	sinine
K- 07 10 04 74	28	23	20	must