

# K-SPIR SCHL B DREH VERSCHRAU

Spiral hose, with swivel adapter fitted at both ends and kink protector

**HANSA FLEX**

## Omadused

<b>Rakendus</b>	Air, gases, oils, greases, fuels, organic and inorganic substances
<b>Töötemperatuur</b>	-40 °C to +100 °C
<b>Ühenduse liik</b>	connection nipples and coupling NW 7,2



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Artikkel

Märgistus	Vooliku sise-Ø (mm)	Vooliku välis-Ø (mm)	Keere	Spiraali välis-Ø (mm)	Keermed	Max. working pressure resistance at 23°C (bar)	max tööpikkus (m)
K- 07 10 07 34	3,1	4,7	R 1/8	38	36	22	2,5
K- 07 10 07 35	3,1	4,7	R 1/8	38	72	22	5,0
K- 07 10 07 36	3,1	4,7	R 1/8	38	108	22	7,5
K- 07 10 07 37	4,8	6,3	R 1/4	75	15	16	2,5
K- 07 10 07 38	4,8	6,3	R 1/4	75	30	16	5,0
K- 07 10 07 39	4,8	6,3	R 1/4	75	45	16	7,5
K- 07 10 07 40	6,3	7,9	R 1/4	75	15	13	2,5
K- 07 10 07 41	6,3	7,9	R 1/4	75	30	13	5,0
K- 07 10 07 42	6,3	7,9	R 1/4	75	45	13	7,5
K- 07 10 07 28	7,9	9,5	R 1/4	115	10	12	2,5
K- 07 10 07 29	7,9	9,5	R 1/4	115	20	12	5,0
K- 07 10 07 30	7,9	9,5	R 1/4	115	30	12	7,5
K- 07 10 07 31	9,5	11,8	R 3/8	140	8	11	2,5
K- 07 10 07 32	9,5	11,8	R 3/8	140	15	11	5,0
K- 07 10 07 33	9,5	11,8	R 3/8	140	23	11	7,5

## Lisatarvikud

<b>K-DREHBARE VERSCHR KNICK</b>	Swivel adapters with kink protector
<b>K-STARRE VERSCHRAUBUNG</b>	Rigid adapters with kink protector