

K-SPIR SCHL DREH VERSCHRAU

Spiral hose, with swivel adapter and kink protector

HANSA FLEX

Omadused

Töötemperatuur -40 °C to +74 °C



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Artikkel

Märgistus	Keere	Vooliku sise-Ø (mm)	Vooliku välis-Ø (mm)	Välise keerme Ø (mm)	Max. working pressure resistance at 23°C (bar)	max tööpikkus (m)
K- 07 10 07 19	G 1/4	5,0	8,0	40	10	3,0
K- 07 10 07 20	G 1/4	5,0	8,0	40	10	6,0
K- 07 10 07 21	G 1/4	5,0	8,0	40	10	7,5
K- 07 10 07 22	G 1/4	6,3	9,5	60	10	3,0
K- 07 10 07 23	G 1/4	6,3	9,5	60	10	6,0
K- 07 10 07 24	G 1/4	6,3	9,5	60	10	7,5
K- 07 10 12 77	G 1/4	6,3	9,5	60	10	10,0
K- 07 10 07 25	G 3/8	8,0	12,0	80	9	3,0
K- 07 10 07 26	G 3/8	8,0	12,0	80	9	6,0
K- 07 10 07 27	G 3/8	8,0	12,0	80	9	7,5
K- 07 10 12 86	G 3/8	8,0	12,0	80	9	10,0

Lisatarvikud

K-DREHBARE VERSCHRAUBUNG Swivel adapters