
K-SPIR SCHL KUPPL SET

Spiral hose and coupling kits

Omadused

Tööröhk	max. 10 bar (to the temperature +20 °C); max. 7 bar (at temperature +40 °C); max. 5 bar (at temperature +60 ° C)
Ühendus	High quality hand quick release coupling of steel for high flow rates For demanding applications with high mechanical wear
Spiraalvoolik	Polyurethane



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For pneumatic applications in challenging industrial environments. High-quality, one-hand quick disconnect coupling made of steel with safety lock to prevent unintentional disconnection. For complex applications susceptible to severe mechanical wear. The outer layer of the hose, which is designed to withstand flying sparks and scorching, has special spark protection. It is therefore ideal for all pneumatic tools used in welding processes.

Artikkel

Märgistus	Vooliku mõõt	Spiraali Ø (mm)	Tööpikkus (m)
K- 07 10 07 56	10 mm x 6,5 mm	52	4,0
K- 07 10 07 57	10 mm x 6,5 mm	52	6,0
K- 07 10 07 58	12 mm x 8 mm	65	8,0

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.