

## Omadused

|                                 |   |
|---------------------------------|---|
| <b>Korpus</b>                   | Amaplast with hinged cover  |
| <b>Korpusesse integreeritud</b> | Hanging eyelets, wall mounting fixing and standing feet   |
| <b>Kaitse</b>                   | Beneath transparent lid (4 MW)  |
| <b>Rakendamine</b>              | Pre-wired   |
| <b>Voolikute sisseviigud</b>    | Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out) |
| <b>Kaitse tüüp</b>              | IP 44   |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

## Artikkel

| Märgistus      | Varustus  | Värv     |
|----------------|---|----------|
| K- 07 10 03 52 | 4 Schuko socket 16 A 2p + E 230 V                                 | kollane  |
| K- 07 10 03 51 | 3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V | hõbedane |

## Lisatarvikud

|                                      |  |
|--------------------------------------|--|
| <b>K-VT 2 KUPPL 7,2 STECKNIP MS</b>  | Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8 |
| <b>K-ZUBEH VSEH 3 KRAFT AIRKRAFT</b> | Accessories for receptacle combinations »3-Kraft« and »airkraft«                               |