

Omadused

Korpus	Amaplast with hinged cover
Korpusesse integreeritud	Hanging eyelets, wall mounting fixing and standing feet
Kaitse	Beneath transparent lid (4 MW)
Rakendamine	Pre-wired
Voolikute sisseviigud	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
Kaitse tüüp	IP 44



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Artikkel

Märgistus	Varustus	Värv
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	kollane
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	hõbedane

Lisatarvikud

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«