

# K-HYDR-KUPPLUNG IG MS

Hydraulic couplings, brass

**HANSA FLEX**

## Omadused

|                                 |  |
|---------------------------------|--|
| <b>Töörõhk</b>                  | See table. All values referred to a medium temperature of 50 °C (static working pressure)  |
| <b>Õhu läbivool</b>             | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8),<br>1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| <b>Aine temperatuur</b>         | -20 °C to +100 °C  |
| <b>Korpus, hüls, ventii</b>     | Brass  |
| <b>Vedru, vedruseib, kuulid</b> | stain less steel   |
| <b>Tihendusmaterjal</b>         | NBR  |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artikkel

| Märgistus      | Ühendus      | NW   | Töörõhk<br>(bar) | Pikkus<br>(mm) | SW<br>(mm) |
|----------------|--------------|------|------------------|----------------|------------|
| K- 07 35 03 81 | G 1/8 female | 4,3  | 250,0            | 48,5           | 14         |
| K- 07 35 03 82 | G 1/4 female | 6,3  | 200,0            | 57,6           | 19         |
| K- 07 35 03 83 | G 3/8 female | 7,5  | 200,0            | 64,2           | 22         |
| K- 07 35 03 84 | G 1/2 female | 11,0 | 150,0            | 76,0           | 27         |
| K- 07 35 03 85 | G 3/4 female | 13,0 | 100,0            | 96,0           | 34         |