


K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Omadused

Töörõhk	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Õhu läbivool	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Aine temperatuur	-20 °C to +90 °C
Korpus, hülss	POM (Delrin), white
Ventiil	Stainless steel 1.4305
Vedru, vedruseib, kuulid	stain less steel
Tihendusmaterjal	NBR



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artikkel

Märgistus	Ühendus	Töörõhk (bar)	Pikkus (mm)	NW	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36