


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Vabastushülss	Anodised aluminium
Vedru, vedruseib, kuulid	stain less steel
Tihendusmaterjal	NBR



Vihje

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Lisaandmed saate soovi korral.

Kirjeldus

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikkel

Märgistus	Ühendus	Värv	Pikkus (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	roheline	45,0	14
K- 07 35 06 81	G 1/4 male	roheline	47,0	17
K- 07 35 06 82	G 1/8 female	roheline	45,0	14
K- 07 35 06 83	G 1/4 female	roheline	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	sinine	45,0	14
K- 07 35 06 89	G 1/4 male	sinine	47,0	17
K- 07 35 06 90	G 1/8 female	sinine	45,0	14
K- 07 35 06 91	G 1/4 female	sinine	47,0	17
K- 07 35 06 92	G 1/8 male	punane	45,0	14
K- 07 35 06 93	G 1/4 male	punane	47,0	17
K- 07 35 06 94	G 1/8 female	punane	45,0	14
K- 07 35 06 95	G 1/4 female	punane	47,0	17