

K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Korpus	Brass
Ventiil	Die-cast zinc, nickel-plated
Vabastushülss	Anodised aluminium
Vedru, vedruseib, kuulid	stain less steel
Tihendusmaterjal	NBR



Vihje

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Lisaandmed saate soovi korral.

Kirjeldus

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikkel

Märgistus	Ühendus	Värv	Pikkus (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	roheline	57,5	19
K- 07 35 08 02	G 3/8 male	roheline	57,5	19
K- 07 35 08 03	G 1/4 female	roheline	55,5	19
K- 07 35 08 04	G 3/8 female	roheline	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	sinine	57,5	19
K- 07 35 08 10	G 3/8 male	sinine	57,5	19
K- 07 35 08 11	G 1/4 female	sinine	55,5	19
K- 07 35 08 12	G 3/8 female	sinine	54,5	19
K- 07 35 08 13	G 1/4 male	punane	57,5	19
K- 07 35 08 14	G 3/8 male	punane	57,5	19
K- 07 35 08 15	G 1/4 female	punane	55,5	19
K- 07 35 08 16	G 3/8 female	punane	54,5	19