

# K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

**HANSA FLEX**

## Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Korpus	Brass
Ventiil	Die-cast zinc, nickel-plated
Vabastushülss	Anodised aluminium
Vedru, vedruseib, kuulid	stain less steel
Tihendusmaterjal	NBR



## Vihje

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Lisaandmed saate soovi korral.

## Kirjeldus

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Artikkel

Märgistus	Ühendus	Värv	Pikkus (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	roheline	57,5	19
K- 07 35 08 02	G 3/8 male	roheline	57,5	19
K- 07 35 08 03	G 1/4 female	roheline	55,5	19
K- 07 35 08 04	G 3/8 female	roheline	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	sinine	57,5	19
K- 07 35 08 10	G 3/8 male	sinine	57,5	19
K- 07 35 08 11	G 1/4 female	sinine	55,5	19
K- 07 35 08 12	G 3/8 female	sinine	54,5	19
K- 07 35 08 13	G 1/4 male	punane	57,5	19
K- 07 35 08 14	G 3/8 male	punane	57,5	19
K- 07 35 08 15	G 1/4 female	punane	55,5	19
K- 07 35 08 16	G 3/8 female	punane	54,5	19