

# K-LKS 7,8 UWB

## Stems and plugs DN 7.8

### Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Materjal	Messing



### Vihje

Lisaandmed saate soovi korral.

### Artikkel

Märgistus	Definitsioon	Värv	SW (mm)
K- 07 35 02 71	Stem, I.D. 6	roheline	-
K- 07 35 02 72	Stem, I.D. 9	roheline	-
K- 07 35 02 73	Stem, I.D. 6	Brown	-
K- 07 35 02 74	Stem, I.D. 9	Brown	-
K- 07 35 02 75	Stem, I.D. 6	sinine	-
K- 07 35 02 76	Stem, I.D. 9	sinine	-
K- 07 35 02 77	Stem, I.D. 6	punane	-
K- 07 35 02 78	Stem, I.D. 9	punane	-
K- 07 35 02 79	Plug G 1/4 male	roheline	17
K- 07 35 02 80	Plug G 3/8 male	roheline	19
K- 07 35 02 81	Plug G 1/4 male	Brown	17
K- 07 35 02 82	Plug G 3/8 male	Brown	19
K- 07 35 02 83	Plug G 1/4 male	sinine	17
K- 07 35 02 84	Plug G 3/8 male	sinine	19
K- 07 35 02 85	Plug G 1/4 male	punane	17
K- 07 35 02 86	Plug G 3/8 male	punane	19