


K-LKS 7,8 UWB

Stems and plugs DN 7.8

Omadused

| | |
|------------------|---|
| Töörõhk | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Õhu läbivool | 1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Aine temperatuur | -20 °C to +100 °C |
| Materjal | Messing |



Vihje

Lisaandmed saate soovi korral.

Artikkel

| Märgistus | Definitsioon | Värv | SW (mm) |
|----------------|-----------------|----------|---------|
| K- 07 35 02 71 | Stem, I.D. 6 | roheline | - |
| K- 07 35 02 72 | Stem, I.D. 9 | roheline | - |
| K- 07 35 02 73 | Stem, I.D. 6 | Brown | - |
| K- 07 35 02 74 | Stem, I.D. 9 | Brown | - |
| K- 07 35 02 75 | Stem, I.D. 6 | sinine | - |
| K- 07 35 02 76 | Stem, I.D. 9 | sinine | - |
| K- 07 35 02 77 | Stem, I.D. 6 | punane | - |
| K- 07 35 02 78 | Stem, I.D. 9 | punane | - |
| K- 07 35 02 79 | Plug G 1/4 male | roheline | 17 |
| K- 07 35 02 80 | Plug G 3/8 male | roheline | 19 |
| K- 07 35 02 81 | Plug G 1/4 male | Brown | 17 |
| K- 07 35 02 82 | Plug G 3/8 male | Brown | 19 |
| K- 07 35 02 83 | Plug G 1/4 male | sinine | 17 |
| K- 07 35 02 84 | Plug G 3/8 male | sinine | 19 |
| K- 07 35 02 85 | Plug G 1/4 male | punane | 17 |
| K- 07 35 02 86 | Plug G 3/8 male | punane | 19 |