

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Omadused

Rakendus	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatuur min.	0 °C
Temperatuur max.	80 °C
Imemisühendus	M 3 female
Rakendamine	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Vedrukäik	5,0 mm



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Suitable for all round or oval suction pads in our standard range.

Artikkel

Märgistus	Vaakumühendus	Pikkus (mm)	Vertikaalkoormus (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400