

# K-SAUGPLATTENAUFHAENGUNG

Flexible suction pad mountings

**HANSA FLEX**

## Omadused

**Rakendus** For handling of workpieces with sloping using large-area vacuum gripper  
Handling of large plates that can sag when lifting  
In combination with spring plungers to compensate height-differences and Unevenness

**Eriiseld tunnused** very good adaptation to oblique workpiece surfaces  
automatic Rückstellung in die Ausgangslage  
vacuum-tight design with integrated protection against damage



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Flexible suction pad mounting. By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

## Artikkel

Märgistus	Sisemine keere 1	Väline keere 2	H (mm)	Materjal	L1 (mm)	L2 (mm)	Nurk W (°)	Vertikaalkoormus (N/m <sup>2</sup> )	Paindemoment (N/m <sup>2</sup> )	SW (mm)
K- 07 45 01 47	G 1/4	M 10 x 1.25	27,0	Steel, rubber	10,5	8,0	12	500	8,0	17
K- 07 45 01 48	G 1/4	G 1/4	27,0	Steel, rubber	12,0	12,0	12	750	10,0	17