

# K-VAKUUMSENSOR DIGITAL

Vacuum sensor, digital

**HANSA FLEX**

## Omadused

|                            |   |
|----------------------------|---|
| <b>Rakendus</b>            | Measurement of vacuum values close to the suction pad<br>Remote evaluation of the signals<br>Processing the output signals, for example, by PLC |
| <b>Vahendid</b>            | dry, oil-free air and non-aggressive gases  |
| <b>Temperatuuri ulatus</b> | 0 - 50 °C   |
| <b>Väljundsignaal</b>      | 1 to 5 analogous to V   |
| <b>Hüsterees</b>           | Fixed: 20 mbar (model with digital sensor)  |
| <b>Kaabli pikkus</b>       | 3 m   |
| <b>Kaitse tüüp</b>         | IP 40   |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

## Artikkel

| Märgistus      | Ühendus  | H<br>(mm) | L<br>(mm) | Mõõteulatus  | Pinge        |
|----------------|----------|-----------|-----------|--------------|--------------|
| K- 07 45 01 57 | M 5 male | 16,9      | 21,0      | -1 bis 0 bar | 10 - 24 V DC |