

K-WV 3/2 5/2 NAMUR

3/2 and 5/2-way spool valves

HANSA FLEX

Omadused

| | |
|-------------------------|--|
| Vahendid | Air, neutral gases (filtered) |
| Rõhuerinevus | 2 - 10 bar |
| lubatud staatiline rõhk | Max. 10 bar |
| Töötemperatuur | -25 °C to +60 °C |
| Elektriühendus | Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580 |
| Korpus | Aluminium, anodised black |
| Tihendusmaterjal | NBR and PUR |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Artikkel

| Märgistus | Pinge | Port 1 | Ühendus 3 + 5 | DN | Läbivool (L/min) |
|----------------|--------------|--------|---------------|----|------------------|
| K- 07 15 00 01 | 230 V, 50 Hz | G 1/4 | G 1/8 | 6 | 700 |
| K- 07 15 00 02 | 24 V DC | G 1/4 | G 1/8 | 6 | 700 |