

K-DRS STANDARD

Standard pressure switches

HANSA FLEX

Omadused

Tüüp	Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions)
Rakendusvaldkond	Air, hydraulic oil, oil emulsions, water
Keskkonnatemperatuur	-25 °C to +85 °C
Elektriühendus	Tab connectors 2 x 6.3 x 0.8
Lülitussagedus	200/min.
Lülituspinge	42 V
Materjal	Galvanised steel



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Artikkel

Märgistus	Keere	Seadistusvahemik	Funktsioon
K- 07 30 24 94	G 1/8	0,3 - 2,0 bar	closer
K- 07 30 24 95	G 1/8	1,0 - 10,0 bar	closer
K- 07 30 24 96	G 1/8	10,0 - 70,0 bar	closer
K- 07 30 24 97	G 1/4	0,3 - 2,0 bar	closer
K- 07 30 24 98	G 1/4	1,0 - 10,0 bar	closer
K- 07 30 24 99	G 1/4	10,0 - 70,0 bar	closer
K- 07 30 24 10	G 1/8	0,3 - 2,0 bar	opener
K- 07 30 24 11	G 1/8	1,0 - 10,0 bar	opener
K- 07 30 24 12	G 1/8	10,0 - 70,0 bar	opener
K- 07 30 24 13	G 1/4	0,3 - 2,0 bar	opener
K- 07 30 24 14	G 1/4	1,0 - 10,0 bar	opener
K- 07 30 24 15	G 1/4	10,0 - 70,0 bar	opener