

K-DRS STANDARD

Standard pressure switches

HANSA FLEX

Omadused

| | |
|------------------------------|--|
| Tüüp | Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions) |
| Rakendusvaldkond | Air, hydraulic oil, oil emulsions, water |
| Keskkonnamtemperatuur | -25 °C to +85 °C |
| Elektriühendus | Tab connectors 2 x 6.3 x 0.8 |
| Lülitussagedus | 200/min. |
| Lülituspinge | 42 V |
| Materjal | Galvanised steel |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Artikkel

| Märgistus | Keere | Seadistusvahemik | Funktsioon |
|----------------|-------|------------------|------------|
| K- 07 30 24 94 | G 1/8 | 0,3 - 2,0 bar | closer |
| K- 07 30 24 95 | G 1/8 | 1,0 - 10,0 bar | closer |
| K- 07 30 24 96 | G 1/8 | 10,0 - 70,0 bar | closer |
| K- 07 30 24 97 | G 1/4 | 0,3 - 2,0 bar | closer |
| K- 07 30 24 98 | G 1/4 | 1,0 - 10,0 bar | closer |
| K- 07 30 24 99 | G 1/4 | 10,0 - 70,0 bar | closer |
| K- 07 30 24 10 | G 1/8 | 0,3 - 2,0 bar | opener |
| K- 07 30 24 11 | G 1/8 | 1,0 - 10,0 bar | opener |
| K- 07 30 24 12 | G 1/8 | 10,0 - 70,0 bar | opener |
| K- 07 30 24 13 | G 1/4 | 0,3 - 2,0 bar | opener |
| K- 07 30 24 14 | G 1/4 | 1,0 - 10,0 bar | opener |
| K- 07 30 24 15 | G 1/4 | 10,0 - 70,0 bar | opener |