

# K-DRS W BAJONETT

Pressure switches - changeover type

**HANSA FLEX**

## Omadused

<b>Tüüp</b>	Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)
<b>Keskonnatemperatuur</b>	-25 °C to +85 °C
<b>Elektriühendus</b>	Bayonet coupling connector Ø 2.5 mm
<b>Lülitussagedus</b>	200/min.
<b>Mõõtepinge</b>	42 V
<b>Funktsioon</b>	Changeover
<b>Materjal</b>	Galvanised steel



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

## Artikkel

Märgistus	Keere	Seadistusvahemik
K- 07 30 28 36	G 1/8	0,5 - 2,0 bar
K- 07 30 28 37	G 1/8	1,0 - 10,0 bar
K- 07 30 28 38	G 1/8	10,0 - 70,0 bar
K- 07 30 28 39	G 1/4	0,5 - 2,0 bar
K- 07 30 28 40	G 1/4	1,0 - 10,0 bar
K- 07 30 28 41	G 1/4	10,0 - 70,0 bar

## Lisatarvikud

**K-WECHSELKONTAKT BANJOETT** Changeover type bayonet coupling