

K-DRS W DREHBAR

Pressure switches, changeover type, turnable

HANSA FLEX

Omadused

Tüüp	Spring-loaded diaphragm (NBR)
Rakendusvaldkond	Air, hydraulic oil, oil emulsions, water
Keskonnatemperatuur	-25 °C to +85 °C
Elektriühendus	Coupling plug Pg 9, DIN 43650
Lülitussagedus	200/min.
Mõõtepinge	250 V
Funktsioon	Changeover
Materjal	Galvanised steel



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Artikkel

Märgistus	Keere	Seadistusvahemik
K- 07 30 28 55	G 1/8	0,3 - 2,0 bar
K- 07 30 28 56	G 1/8	1,0 - 10,0 bar
K- 07 30 28 57	G 1/8	10,0 - 70,0 bar
K- 07 30 28 58	G 1/4	0,3 - 2,0 bar
K- 07 30 28 59	G 1/4	1,0 - 10,0 bar
K- 07 30 28 60	G 1/4	10,0 - 70,0 bar