

# K-DRS W DREHBAR

Pressure switches, changeover type, turnable

**HANSA FLEX**

## Omadused

<b>Tüüp</b>	Spring-loaded diaphragm (NBR)
<b>Rakendusvaldkond</b>	Air, hydraulic oil, oil emulsions, water
<b>Keskonnatemperatuur</b>	-25 °C to +85 °C
<b>Elektriühendus</b>	Coupling plug Pg 9, DIN 43650
<b>Lülitussagedus</b>	200/min.
<b>Mõõtepinge</b>	250 V
<b>Funktsioon</b>	Changeover
<b>Materjal</b>	Galvanised steel



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

## Artikkel

Märgistus	Keere	Seadistusvahemik
K- 07 30 28 55	G 1/8	0,3 - 2,0 bar
K- 07 30 28 56	G 1/8	1,0 - 10,0 bar
K- 07 30 28 57	G 1/8	10,0 - 70,0 bar
K- 07 30 28 58	G 1/4	0,3 - 2,0 bar
K- 07 30 28 59	G 1/4	1,0 - 10,0 bar
K- 07 30 28 60	G 1/4	10,0 - 70,0 bar