

# K-DRS W DREHBAR

Pressure switches, changeover type, turnable

**HANSA FLEX**

## Omadused

|                            |  |
|----------------------------|--|
| <b>Tüüp</b>                | Spring-loaded diaphragm (NBR)            |
| <b>Rakendusvaldkond</b>    | Air, hydraulic oil, oil emulsions, water |
| <b>Keskonnatemperatuur</b> | -25 °C to +85 °C                         |
| <b>Elektriühendus</b>      | Coupling plug Pg 9, DIN 43650            |
| <b>Lülitussagedus</b>      | 200/min.                                 |
| <b>Mõõtepinge</b>          | 250 V                                    |
| <b>Funktsioon</b>          | Changeover                               |
| <b>Materjal</b>            | Galvanised steel                         |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

## Artikkel

| Märgistus      | Keere | Seadistusvahemik |
|----------------|-------|------------------|
| K- 07 30 28 55 | G 1/8 | 0,3 - 2,0 bar    |
| K- 07 30 28 56 | G 1/8 | 1,0 - 10,0 bar   |
| K- 07 30 28 57 | G 1/8 | 10,0 - 70,0 bar  |
| K- 07 30 28 58 | G 1/4 | 0,3 - 2,0 bar    |
| K- 07 30 28 59 | G 1/4 | 1,0 - 10,0 bar   |
| K- 07 30 28 60 | G 1/4 | 10,0 - 70,0 bar  |