


# K-MV G 24 V DC D

Normally closed, 24 V DC (direct current), directly operated

**HANSA FLEX**

## Omadused

<b>Elektriühendus</b>	For Pg 11P connector socket, acc. to DIN 4400
<b>Kaitse tüüp</b>	IP65 (with connector socket fitted)
<b>Aine temperatuur</b>	max. +90 °C with Perbunan-seal; max. +130 °C with FKM-Seal
<b>Korpus, klapipesa</b>	Stainless steel
<b>Sisedetail</b>	Stainless steel
<b>Tihend</b>	Perbunan (NBR) or FKM



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Available versions, Directly operated, Combined operation

## Artikkel

Märgistus	Keere	maksimaalne tööõhk (bar)	NW	Tihendusmaterjal	A (mm)	B (mm)	Ehitustüüp
K- 07 30 23 18	G 1/8	10	2,4	NBR	80,0	30,0	1
K- 07 30 23 20	NPT 1/8	10	2,4	FKM	80,0	30,0	1
K- 07 30 23 19	G 1/4	3	4,0	NBR	80,0	45,0	1
K- 07 30 23 21	G 1/4	3	4,0	FKM	80,0	45,0	1