


# K-MV 3/2 ELK

Solenoid valves

**HANSA FLEX**

## Omadused

<b>Kaitse tüüp</b>	IP65 (with connector socket fitted)
<b>Aine temperatuur</b>	-10 °C to +100 °C
<b>Õhutusühendus</b>	M 5
<b>Rakendus</b>	Compressed air and neutral, non-toxic gases, not suitable for liquids
<b>Töörõhk</b>	min. 0,0 bar; max. 15,0 bar
<b>Elektriline komponent</b>	system connection plug, 180° movement, PG7 exchangeable magnetic heads AC/DC
<b>Nimiläius</b>	1,2 mm
<b>Keskkonnatemperatuur</b>	-10 °C to +60 °C
<b>Korpus</b>	Brass
<b>Sisedetail</b>	Stainless steel
<b>Tihendid</b>	FPM



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Directly operated seat valve with spring return and manual operator. Also suitable for vacuum operation.

## Artikkel

Märgistus	Keere	Pinge	A (mm)	B (mm)
K- 07 30 22 50	G 1/8	230/50 V AC, 50 Hz	58,0	33,0
K- 07 30 22 51	G 1/8	24 V DC	58,0	33,0