


# K-MV O D 24 V DC 1

Normally open, directly operated, 24 V DC (direct current)

**HANSA FLEX**

## Omadused

<b>Elektriühendus</b>	ISO 4400. cable socket (Pg 11P)
<b>Kaitse tüüp</b>	IP65 (with connector socket fitted)
<b>Aine temperatuur</b>	max. +80 °C with Perbunan-seal; max. +130 °C with FKM-Seal
<b>Keerme kirjeldus</b>	G-thread acc. to DIN EN ISO 228-1, Rp-thread acc. to ISO 7-1
<b>Korpus, klapipesa</b>	Brass
<b>Sisedetail</b>	Stainless steel
<b>Tihend</b>	Perbunan (NBR) or FKM



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Standard series, proven over many years, available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Artikkel

Märgistus	Keere	maksimaalne tööõhk (bar)	NW	Tihendusmaterjal	A (mm)	B (mm)	Ehitustüüp
K- 07 30 23 85	Rp 1/8	13	2,4	NBR	75,0	33,0	7
K- 07 30 23 86	G 1/4	6	3,2	NBR	80,0	40,0	2