

# K-HOCHLEIST SICHERHEITSVEN

High-pressure safety valves

**HANSA FLEX**

## Omadused

<b>Rakendus</b>	Compressed air and other non-toxic, neutral and non-flammable gases may escape freely. Not suitable for steam.
<b>Töörõhk</b>	0.5 - 20 bar
<b>Töötemperatuur</b>	max. 180 °C
<b>Vedukate</b>	Brass (up to G 1) / cast iron (powder coated blue G 1 1/4 or larger)
<b>Ventiilikorpus</b>	Brass



## Vihje

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Lisaandmed saate soovi korral.

## Kirjeldus

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100. Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

## Lisateave

Important information: These valves are type-tested and are only allowed to be delivered with a fixed setting.

## Artikkel

Märgistus	Keere	Rõhk	do (mm)	H (mm)	Jõudlus	SW (mm)
K- 07 30 16 19	G 1/2"	0.5 bar	10,0	138,0	53 - 786 Nm3/h	27
K- 07 30 16 20	G 1/2"	0.6 bar	10,0	138,0	-	27
K- 07 30 16 21	G 1/2"	0.8 bar	10,0	138,0	-	27
K- 07 30 16 22	G 1/2"	0.9 bar	10,0	138,0	-	27
K- 07 30 16 23	G 1/2"	1.0 bar	10,0	138,0	-	27
K- 07 30 16 24	G 1/2"	1.1 bar	10,0	138,0	-	27
K- 07 30 16 25	G 1/2"	1.2 bar	10,0	138,0	-	27
K- 07 30 16 26	G 1/2"	1.3 bar	10,0	138,0	-	27
K- 07 30 16 27	G 1/2"	1.5 bar	10,0	138,0	-	27
K- 07 30 16 28	G 1/2"	1.6 bar	10,0	138,0	-	27
K- 07 30 16 29	G 1/2"	1.7 bar	10,0	138,0	-	27
K- 07 30 16 30	G 1/2"	1.8 bar	10,0	138,0	-	27
K- 07 30 16 52	G 1/2"	2.0 bar	10,0	138,0	-	27
K- 07 30 16 53	G 1/2"	2.1 bar	10,0	138,0	-	27
K- 07 30 16 54	G 1/2"	2.2 bar	10,0	138,0	-	27
K- 07 30 16 55	G 1/2"	2.5 bar	10,0	138,0	-	27
K- 07 30 16 56	G 1/2"	2.6 bar	10,0	138,0	-	27
K- 07 30 16 57	G 1/2"	2.7 bar	10,0	138,0	-	27
K- 07 30 16 58	G 1/2"	2.9 bar	10,0	138,0	-	27
K- 07 30 16 65	G 1/2"	3.0 bar	10,0	138,0	-	27
K- 07 30 16 66	G 1/2"	3.1 bar	10,0	138,0	-	27
K- 07 30 16 67	G 1/2"	3.2 bar	10,0	138,0	-	27
K- 07 30 16 68	G 1/2"	3.5 bar	10,0	138,0	-	27
K- 07 30 16 69	G 1/2"	3.9 bar	10,0	138,0	-	27
K- 07 30 16 71	G 1/2"	4.0 bar	10,0	138,0	-	27
K- 07 30 16 72	G 1/2"	4.3 bar	10,0	138,0	-	27
K- 07 30 16 73	G 1/2"	4.5 bar	10,0	138,0	-	27
K- 07 30 16 74	G 1/2"	5.0 bar	10,0	138,0	-	27
K- 07 30 16 75	G 1/2"	5.2 bar	10,0	138,0	-	27
K- 07 30 16 76	G 1/2"	5.3 bar	10,0	138,0	-	27
K- 07 30 16 77	G 1/2"	5.4 bar	10,0	138,0	-	27
K- 07 30 16 78	G 1/2"	5.5 bar	10,0	138,0	-	27
K- 07 30 16 79	G 1/2"	6.0 bar	10,0	138,0	-	27
K- 07 30 16 80	G 1/2"	6.3 bar	10,0	138,0	-	27
K- 07 30 16 81	G 1/2"	6.4 bar	10,0	138,0	-	27
K- 07 30 16 82	G 1/2"	6.5 bar	10,0	138,0	-	27



Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.

16.07.2024

HANSA-FLEX AG

www.hansa-flex.com

# K-HOCHLEIST SICHERHEITSVEN

High-pressure safety valves

**HANSA FLEX**

Artikkel	Märgistus	Keere	Rõhk	do (mm)	H (mm)	Jõudlus	SW (mm)
K- 07 30 16 83		G 1/2"	6.6 bar	10,0	138,0	-	27
K- 07 30 16 84		G 1/2"	7.0 bar	10,0	138,0	-	27
K- 07 30 16 85		G 1/2"	7.5 bar	10,0	138,0	-	27
K- 07 30 16 86		G 1/2"	7.9 bar	10,0	138,0	-	27
K- 07 30 16 87		G 1/2"	8.0 bar	10,0	138,0	-	27
K- 07 30 16 88		G 1/2"	8.5 bar	10,0	138,0	-	27
K- 07 30 16 89		G 1/2"	9.0 bar	10,0	138,0	-	27
K- 07 30 16 90		G 1/2"	9.1 bar	10,0	138,0	-	27
K- 07 30 16 91		G 1/2"	9.5 bar	10,0	138,0	-	27
K- 07 30 16 31		G 1/2"	10.0 bar	10,0	138,0	-	27
K- 07 30 16 32		G 1/2"	10.5 bar	10,0	138,0	-	27
K- 07 30 16 33		G 1/2"	10.9 bar	10,0	138,0	-	27
K- 07 30 16 34		G 1/2"	11.0 bar	10,0	138,0	-	27
K- 07 30 16 35		G 1/2"	11.5 bar	10,0	138,0	-	27
K- 07 30 16 36		G 1/2"	11.7 bar	10,0	138,0	-	27
K- 07 30 16 37		G 1/2"	12.0 bar	10,0	138,0	-	27
K- 07 30 16 38		G 1/2"	12.5 bar	10,0	138,0	53 - 786 Nm3/h	27
K- 07 30 16 39		G 1/2"	13.0 bar	10,0	138,0	-	27
K- 07 30 16 40		G 1/2"	13.5 bar	10,0	138,0	-	27
K- 07 30 16 41		G 1/2"	14.0 bar	10,0	138,0	-	27
K- 07 30 16 42		G 1/2"	14.3 bar	10,0	138,0	-	27
K- 07 30 16 43		G 1/2"	14.5 bar	10,0	138,0	-	27
K- 07 30 16 44		G 1/2"	14.7 bar	10,0	138,0	-	27
K- 07 30 16 45		G 1/2"	15.0 bar	10,0	138,0	-	27
K- 07 30 16 46		G 1/2"	16.0 bar	10,0	138,0	-	27
K- 07 30 16 47		G 1/2"	16.5 bar	10,0	138,0	-	27
K- 07 30 16 48		G 1/2"	17.0 bar	10,0	138,0	-	27
K- 07 30 16 49		G 1/2"	18.0 bar	10,0	138,0	-	27
K- 07 30 16 50		G 1/2"	19.5 bar	10,0	138,0	-	27
K- 07 30 16 51		G 1/2"	19.8 bar	10,0	138,0	-	27
K- 07 30 16 59		G 1/2"	20.0 bar	10,0	138,0	-	27
K- 07 30 16 60		G 1/2"	21.0 bar	10,0	138,0	-	27
K- 07 30 16 61		G 1/2"	24.0 bar	10,0	138,0	-	27
K- 07 30 16 62		G 1/2"	24.5 bar	10,0	138,0	-	27
K- 07 30 16 63		G 1/2"	25.0 bar	10,0	138,0	-	27
K- 07 30 16 64		G 1/2"	26.0 bar	10,0	138,0	-	27
K- 07 30 16 70		G 1/2"	30.0 bar	10,0	138,0	-	27
K- 07 30 16 92		G 3/4"	0.5 bar	15,0	153,0	79 - 1172 Nm3/h	36
K- 07 30 16 93		G 3/4"	0.6 bar	15,0	153,0	-	36
K- 07 30 16 94		G 3/4"	0.7 bar	15,0	153,0	-	36
K- 07 30 16 95		G 3/4"	0.8 bar	15,0	153,0	-	36
K- 07 30 16 96		G 3/4"	0.9 bar	15,0	153,0	-	36
K- 07 30 16 97		G 3/4"	1.0 bar	15,0	153,0	-	36
K- 07 30 16 98		G 3/4"	1.2 bar	15,0	153,0	-	36
K- 07 30 16 99		G 3/4"	1.3 bar	15,0	153,0	-	36
K- 07 30 17 00		G 3/4"	1.5 bar	15,0	153,0	-	36
K- 07 30 17 01		G 3/4"	1.6 bar	15,0	153,0	-	36
K- 07 30 17 24		G 3/4"	2.0 bar	15,0	153,0	-	36
K- 07 30 17 25		G 3/4"	2.5 bar	15,0	153,0	-	36
K- 07 30 17 26		G 3/4"	2.6 bar	15,0	153,0	-	36
K- 07 30 17 27		G 3/4"	2.7 bar	15,0	153,0	-	36
K- 07 30 17 32		G 3/4"	3.0 bar	15,0	153,0	-	36
K- 07 30 17 33		G 3/4"	3.5 bar	15,0	153,0	-	36
K- 07 30 17 35		G 3/4"	4.0 bar	15,0	153,0	-	36
K- 07 30 17 36		G 3/4"	4.5 bar	15,0	153,0	-	36
K- 07 30 17 37		G 3/4"	5.0 bar	15,0	153,0	-	36
K- 07 30 17 38		G 3/4"	6.0 bar	15,0	153,0	-	36
K- 07 30 17 39		G 3/4"	6.4 bar	15,0	153,0	-	36
K- 07 30 17 40		G 3/4"	6.5 bar	15,0	153,0	-	36
K- 07 30 17 41		G 3/4"	6.8 bar	15,0	153,0	-	36
K- 07 30 17 42		G 3/4"	7.0 bar	15,0	153,0	-	36
K- 07 30 17 43		G 3/4"	8.0 bar	15,0	153,0	-	36
K- 07 30 17 44		G 3/4"	8.3 bar	15,0	153,0	-	36



Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.

16.07.2024

HANSA-FLEX AG

[www.hansa-flex.com](http://www.hansa-flex.com)

2

# K-HOCHLEIST SICHERHEITSVEN

High-pressure safety valves

**HANSA FLEX**

Artikkel	Märgistus	Keere	Rõhk	do (mm)	H (mm)	Jõudlus	SW (mm)
K- 07 30 17 45	G 3/4"		8.5 bar	15,0	153,0	-	36
K- 07 30 17 46	G 3/4"		8.6 bar	15,0	153,0	-	36
K- 07 30 17 47	G 3/4"		8.8 bar	15,0	153,0	-	36
K- 07 30 17 48	G 3/4"		9.0 bar	15,0	153,0	-	36
K- 07 30 17 49	G 3/4"		9.3 bar	15,0	153,0	-	36
K- 07 30 17 50	G 3/4"		9.5 bar	15,0	153,0	-	36
K- 07 30 17 02	G 3/4"		10.0 bar	15,0	153,0	-	36
K- 07 30 17 03	G 3/4"		10.5 bar	15,0	153,0	-	36
K- 07 30 17 04	G 3/4"		10.6 bar	15,0	153,0	-	36
K- 07 30 17 05	G 3/4"		11.0 bar	15,0	153,0	-	36
K- 07 30 17 06	G 3/4"		11.5 bar	15,0	153,0	-	36
K- 07 30 17 07	G 3/4"		12.0 bar	15,0	153,0	-	36
K- 07 30 17 08	G 3/4"		12.5 bar	15,0	153,0	79 - 1172 Nm3/h	36
K- 07 30 17 09	G 3/4"		13.0 bar	15,0	153,0	-	36
K- 07 30 17 10	G 3/4"		14.0 bar	15,0	153,0	-	36
K- 07 30 17 11	G 3/4"		14.2 bar	15,0	153,0	-	36
K- 07 30 17 12	G 3/4"		14.5 bar	15,0	153,0	-	36
K- 07 30 17 13	G 3/4"		15.0 bar	15,0	153,0	-	36
K- 07 30 17 14	G 3/4"		15.5 bar	15,0	153,0	-	36
K- 07 30 17 15	G 3/4"		15.8 bar	15,0	153,0	-	36
K- 07 30 17 16	G 3/4"		16.0 bar	15,0	153,0	-	36
K- 07 30 17 17	G 3/4"		16.5 bar	15,0	153,0	-	36
K- 07 30 17 18	G 3/4"		17.0 bar	15,0	153,0	-	36
K- 07 30 17 19	G 3/4"		17.5 bar	15,0	153,0	-	36
K- 07 30 17 20	G 3/4"		18.0 bar	15,0	153,0	-	36
K- 07 30 17 21	G 3/4"		18.5 bar	15,0	153,0	-	36
K- 07 30 17 22	G 3/4"		19.0 bar	15,0	153,0	-	36
K- 07 30 17 23	G 3/4"		19.5 bar	15,0	153,0	-	36
K- 07 30 17 28	G 3/4"		20.0 bar	15,0	153,0	-	36
K- 07 30 17 29	G 3/4"		21.0 bar	15,0	153,0	-	36
K- 07 30 17 30	G 3/4"		22.0 bar	15,0	153,0	-	36
K- 07 30 17 31	G 3/4"		25.0 bar	15,0	153,0	-	36
K- 07 30 17 34	G 3/4"		30.0 bar	15,0	153,0	-	36
K- 07 30 17 51	G 1"		0.5 bar	20,0	185,0	213 - 3148 Nm3/h	41
K- 07 30 17 52	G 1"		0.6 bar	20,0	185,0	-	41
K- 07 30 17 53	G 1"		0.7 bar	20,0	185,0	-	41
K- 07 30 17 54	G 1"		0.8 bar	20,0	185,0	-	41
K- 07 30 17 55	G 1"		0.9 bar	20,0	185,0	-	41
K- 07 30 17 56	G 1"		1.0 bar	20,0	185,0	-	41
K- 07 30 17 57	G 1"		1.2 bar	20,0	185,0	-	41
K- 07 30 17 58	G 1"		1.3 bar	20,0	185,0	-	41
K- 07 30 17 59	G 1"		1.5 bar	20,0	185,0	-	41
K- 07 30 17 60	G 1"		1.6 bar	20,0	185,0	-	41
K- 07 30 17 61	G 1"		1.7 bar	20,0	185,0	-	41
K- 07 30 17 62	G 1"		1.8 bar	20,0	185,0	-	41
K- 07 30 17 81	G 1"		2.0 bar	20,0	185,0	-	41
K- 07 30 17 82	G 1"		2.2 bar	20,0	185,0	-	41
K- 07 30 17 83	G 1"		2.3 bar	20,0	185,0	-	41
K- 07 30 17 84	G 1"		2.5 bar	20,0	185,0	-	41
K- 07 30 17 85	G 1"		2.7 bar	20,0	185,0	-	41
K- 07 30 17 86	G 1"		2.9 bar	20,0	185,0	-	41
K- 07 30 17 92	G 1"		3.0 bar	20,0	185,0	-	41
K- 07 30 17 93	G 1"		3.2 bar	20,0	185,0	-	41
K- 07 30 17 94	G 1"		3.4 bar	20,0	185,0	-	41
K- 07 30 17 95	G 1"		3.5 bar	20,0	185,0	-	41
K- 07 30 17 96	G 1"		3.9 bar	20,0	185,0	-	41
K- 07 30 17 98	G 1"		4.0 bar	20,0	185,0	-	41
K- 07 30 17 99	G 1"		4.5 bar	20,0	185,0	-	41
K- 07 30 18 00	G 1"		4.7 bar	20,0	185,0	-	41
K- 07 30 18 01	G 1"		5.0 bar	20,0	185,0	-	41
K- 07 30 18 02	G 1"		5.4 bar	20,0	185,0	-	41
K- 07 30 18 03	G 1"		5.5 bar	20,0	185,0	-	41
K- 07 30 18 04	G 1"		5.7 bar	20,0	185,0	-	41



Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.

16.07.2024

HANSA-FLEX AG

www.hansa-flex.com

3

# K-HOCHLEIST SICHERHEITSVEN

High-pressure safety valves

**HANSA FLEX**

Artikkel	Märgistus	Keere	Rõhk	do (mm)	H (mm)	Jõudlus	SW (mm)
K- 07 30 18 05	G 1"		6.0 bar	20,0	185,0	-	41
K- 07 30 18 06	G 1"		6.2 bar	20,0	185,0	-	41
K- 07 30 18 07	G 1"		6.3 bar	20,0	185,0	-	41
K- 07 30 18 08	G 1"		6.5 bar	20,0	185,0	-	41
K- 07 30 18 09	G 1"		6.6 bar	20,0	185,0	-	41
K- 07 30 18 10	G 1"		6.9 bar	20,0	185,0	-	41
K- 07 30 18 11	G 1"		7.0 bar	20,0	185,0	-	41
K- 07 30 18 12	G 1"		7.2 bar	-	-	-	-
K- 07 30 18 13	G 1"		7.5 bar	20,0	185,0	-	41
K- 07 30 18 14	G 1"		7.6 bar	20,0	185,0	-	41
K- 07 30 18 15	G 1"		7.8 bar	20,0	185,0	-	41
K- 07 30 18 16	G 1"		8.0 bar	20,0	185,0	-	41
K- 07 30 18 17	G 1"		8.2 bar	20,0	185,0	-	41
K- 07 30 18 18	G 1"		8.5 bar	20,0	185,0	-	41
K- 07 30 18 19	G 1"		8.8 bar	20,0	185,0	-	41
K- 07 30 18 20	G 1"		9.0 bar	20,0	185,0	-	41
K- 07 30 18 21	G 1"		9.2 bar	20,0	185,0	-	41
K- 07 30 18 22	G 1"		9.5 bar	20,0	185,0	-	41
K- 07 30 18 23	G 1"		9.8 bar	20,0	185,0	-	41
K- 07 30 17 63	G 1"		10.0 bar	20,0	185,0	-	41
K- 07 30 17 64	G 1"		10.5 bar	20,0	185,0	-	41
K- 07 30 17 65	G 1"		11.0 bar	20,0	185,0	-	41
K- 07 30 17 66	G 1"		11.5 bar	20,0	185,0	-	41
K- 07 30 17 67	G 1"		12.0 bar	20,0	185,0	-	41
K- 07 30 17 68	G 1"		12.5 bar	20,0	185,0	213 - 3148 Nm3/h	41
K- 07 30 17 69	G 1"		13.0 bar	20,0	185,0	-	41
K- 07 30 17 70	G 1"		13.5 bar	20,0	185,0	-	41
K- 07 30 17 71	G 1"		14.0 bar	20,0	185,0	-	41
K- 07 30 17 72	G 1"		14.5 bar	20,0	185,0	-	41
K- 07 30 17 73	G 1"		14.8 bar	20,0	185,0	-	41
K- 07 30 17 74	G 1"		15.0 bar	20,0	185,0	-	41
K- 07 30 17 75	G 1"		15.3 bar	20,0	185,0	-	41
K- 07 30 17 76	G 1"		15.5 bar	20,0	185,0	-	41
K- 07 30 17 77	G 1"		16.0 bar	20,0	185,0	-	41
K- 07 30 17 78	G 1"		16.5 bar	20,0	185,0	-	41
K- 07 30 17 79	G 1"		17.0 bar	20,0	185,0	-	41
K- 07 30 17 80	G 1"		18.0 bar	20,0	185,0	-	41
K- 07 30 17 87	G 1"		20.0 bar	20,0	185,0	-	41
K- 07 30 17 88	G 1"		21.0 bar	20,0	185,0	-	41
K- 07 30 17 89	G 1"		25.0 bar	20,0	185,0	-	41
K- 07 30 17 90	G 1"		27.0 bar	20,0	185,0	-	41
K- 07 30 17 91	G 1"		28.0 bar	20,0	185,0	-	41
K- 07 30 17 97	G 1"		30.0 bar	20,0	185,0	-	41
K- 07 30 18 24	G 1 1/4"		0.5 bar	25,0	231,0	334 - 4930 Nm3/h	50
K- 07 30 18 25	G 1 1/4"		0.7 bar	25,0	231,0	-	50
K- 07 30 18 26	G 1 1/4"		0.9 bar	25,0	231,0	-	50
K- 07 30 18 27	G 1 1/4"		1.0 bar	25,0	231,0	-	50
K- 07 30 18 28	G 1 1/4"		1.2 bar	25,0	231,0	-	50
K- 07 30 18 29	G 1 1/4"		1.3 bar	25,0	231,0	-	50
K- 07 30 18 30	G 1 1/4"		1.5 bar	25,0	231,0	-	50
K- 07 30 18 31	G 1 1/4"		1.8 bar	25,0	231,0	-	50
K- 07 30 18 47	G 1 1/4"		2.0 bar	25,0	231,0	-	50
K- 07 30 18 48	G 1 1/4"		2.1 bar	25,0	231,0	-	50
K- 07 30 18 49	G 1 1/4"		2.2 bar	25,0	231,0	-	50
K- 07 30 18 50	G 1 1/4"		2.5 bar	25,0	231,0	-	50
K- 07 30 18 54	G 1 1/4"		3.0 bar	25,0	231,0	-	50
K- 07 30 18 55	G 1 1/4"		3.1 bar	25,0	231,0	-	50
K- 07 30 18 56	G 1 1/4"		5.0 bar	25,0	231,0	-	50
K- 07 30 18 57	G 1 1/4"		5.7 bar	25,0	231,0	-	50
K- 07 30 18 58	G 1 1/4"		6.0 bar	25,0	231,0	-	50
K- 07 30 18 59	G 1 1/4"		6.6 bar	25,0	231,0	-	50
K- 07 30 18 60	G 1 1/4"		6.8 bar	25,0	231,0	-	50
K- 07 30 18 61	G 1 1/4"		7.0 bar	25,0	231,0	-	50



Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.

16.07.2024

HANSA-FLEX AG

www.hansa-flex.com

4

# K-HOCHLEIST SICHERHEITSVEN

High-pressure safety valves

**HANSA FLEX**

Artikkel	Märgistus	Keere	Rõhk	do (mm)	H (mm)	Jõudlus	SW (mm)
K- 07 30 18 62		G 1 1/4"	7.5 bar	25,0	231,0	-	50
K- 07 30 18 63		G 1 1/4"	7.7 bar	25,0	231,0	-	50
K- 07 30 18 64		G 1 1/4"	8.0 bar	25,0	231,0	-	50
K- 07 30 18 65		G 1 1/4"	8.2 bar	25,0	231,0	-	50
K- 07 30 18 66		G 1 1/4"	8.5 bar	25,0	231,0	-	50
K- 07 30 18 67		G 1 1/4"	8.8 bar	25,0	231,0	-	50
K- 07 30 18 68		G 1 1/4"	9.0 bar	25,0	231,0	-	50
K- 07 30 18 69		G 1 1/4"	9.3 bar	25,0	231,0	-	50
K- 07 30 18 32		G 1 1/4"	10.0 bar	25,0	231,0	-	50
K- 07 30 18 33		G 1 1/4"	10.5 bar	25,0	231,0	-	50
K- 07 30 18 34		G 1 1/4"	11.0 bar	25,0	231,0	-	50
K- 07 30 18 35		G 1 1/4"	11.5 bar	25,0	231,0	-	50
K- 07 30 18 36		G 1 1/4"	11.8 bar	25,0	231,0	-	50
K- 07 30 18 37		G 1 1/4"	12.0 bar	25,0	231,0	-	50
K- 07 30 18 38		G 1 1/4"	13.0 bar	25,0	231,0	-	50
K- 07 30 18 39		G 1 1/4"	13.2 bar	25,0	231,0	334 - 4930 Nm3/h	50
K- 07 30 18 40		G 1 1/4"	14.0 bar	25,0	231,0	-	50
K- 07 30 18 41		G 1 1/4"	14.5 bar	25,0	231,0	-	50
K- 07 30 18 42		G 1 1/4"	15.0 bar	25,0	231,0	-	50
K- 07 30 18 43		G 1 1/4"	16.0 bar	25,0	231,0	-	50
K- 07 30 18 44		G 1 1/4"	17.0 bar	25,0	231,0	-	50
K- 07 30 18 45		G 1 1/4"	17.5 bar	25,0	231,0	-	50
K- 07 30 18 46		G 1 1/4"	18.0 bar	25,0	231,0	-	50
K- 07 30 18 51		G 1 1/4"	20.0 bar	25,0	231,0	-	50
K- 07 30 18 52		G 1 1/4"	23.0 bar	25,0	231,0	-	50
K- 07 30 18 53		G 1 1/4"	25.0 bar	25,0	231,0	-	50
K- 07 30 18 70		G 1 1/2"	0.5 bar	32,0	293,0	546 - 8060 Nm3/h	60
K- 07 30 18 71		G 1 1/2"	0.6 bar	32,0	293,0	-	60
K- 07 30 18 72		G 1 1/2"	0.8 bar	32,0	293,0	-	60
K- 07 30 18 73		G 1 1/2"	0.9 bar	32,0	293,0	-	60
K- 07 30 18 74		G 1 1/2"	1.0 bar	32,0	293,0	-	60
K- 07 30 18 75		G 1 1/2"	1.2 bar	32,0	293,0	-	60
K- 07 30 18 76		G 1 1/2"	1.5 bar	32,0	293,0	-	60
K- 07 30 18 87		G 1 1/2"	2.0 bar	32,0	293,0	-	60
K- 07 30 18 88		G 1 1/2"	2.1 bar	32,0	293,0	-	60
K- 07 30 18 89		G 1 1/2"	2.3 bar	32,0	293,0	-	60
K- 07 30 18 90		G 1 1/2"	2.5 bar	32,0	293,0	-	60
K- 07 30 18 91		G 1 1/2"	2.6 bar	32,0	293,0	-	60
K- 07 30 18 93		G 1 1/2"	3.0 bar	32,0	293,0	-	60
K- 07 30 18 94		G 1 1/2"	3.2 bar	32,0	293,0	-	60
K- 07 30 18 95		G 1 1/2"	3.3 bar	32,0	293,0	-	60
K- 07 30 18 96		G 1 1/2"	3.5 bar	32,0	293,0	-	60
K- 07 30 18 97		G 1 1/2"	3.7 bar	32,0	293,0	-	60
K- 07 30 18 98		G 1 1/2"	3.9 bar	32,0	293,0	-	60
K- 07 30 18 99		G 1 1/2"	4.0 bar	32,0	293,0	-	60
K- 07 30 19 00		G 1 1/2"	4.2 bar	32,0	293,0	-	60
K- 07 30 19 01		G 1 1/2"	4.5 bar	32,0	293,0	-	60
K- 07 30 19 02		G 1 1/2"	5.0 bar	32,0	293,0	-	60
K- 07 30 19 03		G 1 1/2"	5.5 bar	32,0	293,0	-	60
K- 07 30 19 04		G 1 1/2"	6.0 bar	32,0	293,0	-	60
K- 07 30 19 05		G 1 1/2"	6.5 bar	32,0	293,0	-	60
K- 07 30 19 06		G 1 1/2"	6.8 bar	32,0	293,0	-	60
K- 07 30 19 07		G 1 1/2"	7.0 bar	32,0	293,0	-	60
K- 07 30 19 08		G 1 1/2"	8.0 bar	32,0	293,0	-	60
K- 07 30 19 09		G 1 1/2"	8.2 bar	32,0	293,0	-	60
K- 07 30 19 10		G 1 1/2"	8.4 bar	32,0	293,0	-	60
K- 07 30 19 11		G 1 1/2"	8.5 bar	32,0	293,0	-	60
K- 07 30 19 12		G 1 1/2"	8.6 bar	32,0	293,0	-	60
K- 07 30 19 13		G 1 1/2"	8.8 bar	32,0	293,0	-	60
K- 07 30 19 14		G 1 1/2"	9.0 bar	32,0	293,0	-	60
K- 07 30 19 15		G 1 1/2"	9.3 bar	32,0	293,0	-	60
K- 07 30 19 16		G 1 1/2"	9.5 bar	32,0	293,0	-	60
K- 07 30 18 78		G 1 1/2"	10.0 bar	32,0	293,0	-	60



Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.

16.07.2024

HANSA-FLEX AG

[www.hansa-flex.com](http://www.hansa-flex.com)

# K-HOCHLEIST SICHERHEITSVEN

High-pressure safety valves

**HANSA FLEX**

Artikkel	Märgistus	Keere	Rõhk	do (mm)	H (mm)	Jõudlus	SW (mm)
K- 07 30 18 79		G 1 1/2"	10.4 bar	32,0	293,0	-	60
K- 07 30 18 80		G 1 1/2"	10.5 bar	32,0	293,0	-	60
K- 07 30 18 81		G 1 1/2"	11.0 bar	32,0	293,0	-	60
K- 07 30 18 82		G 1 1/2"	12.0 bar	32,0	293,0	-	60
K- 07 30 18 83		G 1 1/2"	15.0 bar	32,0	293,0	546 - 8060 Nm3/h	60
K- 07 30 18 84		G 1 1/2"	16.0 bar	32,0	293,0	-	60
K- 07 30 18 85		G 1 1/2"	17.0 bar	32,0	293,0	-	60
K- 07 30 18 86		G 1 1/2"	19.0 bar	32,0	293,0	-	60
K- 07 30 18 92		G 1 1/2"	20.0 bar	32,0	293,0	-	60
K- 07 30 19 17		G 2"	0.5 bar	40,0	367,0	855 - 12615 Nm3/h	80
K- 07 30 19 18		G 2"	0.8 bar	40,0	367,0	-	80
K- 07 30 19 19		G 2"	0.9 bar	40,0	367,0	-	80
K- 07 30 19 20		G 2"	1.0 bar	40,0	367,0	-	80
K- 07 30 19 21		G 2"	1.3 bar	40,0	367,0	-	80
K- 07 30 19 22		G 2"	1.5 bar	40,0	367,0	-	80
K- 07 30 19 23		G 2"	1.6 bar	40,0	367,0	-	80
K- 07 30 19 24		G 2"	1.8 bar	40,0	367,0	-	80
K- 07 30 19 38		G 2"	2.0 bar	40,0	367,0	-	80
K- 07 30 19 39		G 2"	2.1 bar	40,0	367,0	-	80
K- 07 30 19 40		G 2"	2.5 bar	40,0	367,0	-	80
K- 07 30 19 41		G 2"	2.6 bar	40,0	367,0	-	80
K- 07 30 19 42		G 2"	2.8 bar	40,0	367,0	-	80
K- 07 30 19 44		G 2"	3.0 bar	40,0	367,0	-	80
K- 07 30 19 45		G 2"	3.5 bar	40,0	367,0	-	80
K- 07 30 19 46		G 2"	3.7 bar	40,0	367,0	-	80
K- 07 30 19 47		G 2"	3.8 bar	40,0	367,0	-	80
K- 07 30 19 48		G 2"	3.9 bar	40,0	367,0	-	80
K- 07 30 19 49		G 2"	4.0 bar	40,0	367,0	-	80
K- 07 30 19 50		G 2"	4.5 bar	40,0	367,0	-	80
K- 07 30 19 51		G 2"	4.8 bar	40,0	367,0	-	80
K- 07 30 19 52		G 2"	5.0 bar	40,0	367,0	-	80
K- 07 30 19 53		G 2"	5.5 bar	40,0	367,0	-	80
K- 07 30 19 54		G 2"	6.0 bar	40,0	367,0	-	80
K- 07 30 19 55		G 2"	6.4 bar	40,0	367,0	-	80
K- 07 30 19 56		G 2"	6.8 bar	40,0	367,0	-	80
K- 07 30 19 57		G 2"	7.0 bar	40,0	367,0	-	80
K- 07 30 19 58		G 2"	7.2 bar	40,0	367,0	-	80
K- 07 30 19 59		G 2"	7.5 bar	40,0	367,0	-	80
K- 07 30 19 60		G 2"	8.0 bar	40,0	367,0	-	80
K- 07 30 19 61		G 2"	8.5 bar	40,0	367,0	-	80
K- 07 30 19 62		G 2"	8.8 bar	40,0	367,0	-	80
K- 07 30 19 63		G 2"	9.0 bar	40,0	367,0	-	80
K- 07 30 19 64		G 2"	9.3 bar	40,0	367,0	-	80
K- 07 30 19 65		G 2"	9.5 bar	40,0	367,0	-	80
K- 07 30 19 66		G 2"	9.7 bar	40,0	367,0	-	80
K- 07 30 19 67		G 2"	9.8 bar	40,0	367,0	-	80
K- 07 30 19 25		G 2"	10.0 bar	40,0	367,0	-	80
K- 07 30 19 26		G 2"	10.2 bar	40,0	367,0	-	80
K- 07 30 19 27		G 2"	10.5 bar	40,0	367,0	-	80
K- 07 30 19 28		G 2"	11.0 bar	40,0	367,0	-	80
K- 07 30 19 29		G 2"	12.0 bar	40,0	367,0	-	80
K- 07 30 19 30		G 2"	13.0 bar	40,0	367,0	855 - 12615 Nm3/h	80
K- 07 30 19 31		G 2"	14.0 bar	40,0	367,0	-	80
K- 07 30 19 32		G 2"	15.0 bar	40,0	367,0	-	80
K- 07 30 19 33		G 2"	16.0 bar	40,0	367,0	-	80
K- 07 30 19 34		G 2"	17.0 bar	40,0	367,0	-	80
K- 07 30 19 35		G 2"	17.6 bar	40,0	367,0	-	80
K- 07 30 19 36		G 2"	18.0 bar	40,0	367,0	-	80
K- 07 30 19 37		G 2"	19.0 bar	40,0	367,0	-	80
K- 07 30 19 43		G 2"	20.0 bar	40,0	367,0	-	80
K- 07 30 18 77		G 1 1/2"	1.8 bar	32,0	293,0	-	60