

K-ANSCHLUSSNIP FLACHSAUG AG

Connection nipples for flat suction pads

HANSA FLEX

Omadused

imuri läbimõõdu jaoks 20 mm



Vihje

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

Lisateave

Socket connectors suitable for vacuum («click-clock» series) see page All PA/PE/PU hoses up to size 12 x 9 mm are suitable for vacuum. See page

Artikkel

| Märgistus | Keere | Pikkus (mm) | NW |
|----------------|------------|----------------|-----|
| K- 07 45 00 15 | M 5 male | 5,0 | 2,0 |
| K- 07 45 00 16 | G 1/4 male | 5,0 | 5,5 |
| K- 07 45 00 17 | G 1/8 male | 3,0 | 2,0 |
| K- 07 45 00 18 | G 1/8 male | 5,0 | 2,0 |
| K- 07 45 00 19 | G 1/8 male | 5,0 | 2,0 |
| K- 07 45 00 20 | G 1/8 male | 4,5 | 2,4 |
| K- 07 45 00 21 | G 1/8 male | 5,0 | 2,4 |

on järgnevate toodete lisatarvikud

| | |
|----------------------------|---|
| K-FLACHSAUGER RUND NBR | Flat suction pads, round, material NBR |
| K-FLACHSAUGER RUND SILIKON | Flat suction pads, round, material silicone |