


K-SPV DOPPEL

Check valves, double-acting

HANSA FLEX

Omadused

Töörõhk	max 10 baari
Juhtimisrõhk	min. 3.0 bar, max. 8 bar with double-acting actuator; min. 4.2 bar, max. 8 bar for single-drive
Temperatuur	-20 °C to +80 °C (NBR); -20 °C to +150 °C (FKM)
Ühendus	NAMUR-Interface, direct: 2 x G 1/8
Paigaldusasend	Any
Korpus, sisedetailid	Nickel-plated brass
Vedru	Stainless-steel
Tihendusmaterjal	Perbunan (NBR) or FKM (FPM)



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.
These valves have a full bore.

Artikkel

Märgistus	DN	Keere	Tihendusmaterjal	H (mm)	L (mm)
K- 07 30 25 37	10	Rp 3/8	NBR	46,0	98,0
K- 07 30 25 38	15	Rp 1/2	NBR	51,7	112,0
K- 07 30 25 39	20	Rp 3/4	NBR	63,5	135,0
K- 07 30 25 40	25	Rp 1	NBR	69,0	143,0
K- 07 30 25 41	10	Rp 3/8	FKM	46,0	98,0
K- 07 30 25 42	15	Rp 1/2	FKM	51,7	112,0
K- 07 30 25 43	20	Rp 3/4	FKM	63,5	135,0
K- 07 30 25 44	25	Rp 1	FKM	69,0	143,0