
K-INLINE-DRG AG IG M SEKUNDAERENTLU

Inline pressure regulators, female/male thread, self-relieving

Omadused

Tööröhk	Max. 25 bar
Temperatuuri ulatus	0 °C to +80 °C
Korpus	Aluminium
ülejäänud osad	Stainless steel, nitrile rubber, brass





Vihje

Lisaandmed saate soovi korral.

Kirjeldus

The majority of pneumatic tools are connected directly to the compressed air supply by means of a quick disconnect coupling, in other words they tend to be supplied with a higher pressure than is actually required. Which increases consumption and leads to tool overload. Added safety is provided by the automatic self-relieving function. If the tool is disconnected from the hose, it continues to work for a short period, even though it has been switched off, owing to the residual pressure that is present on the tool side.
Inadvertent operation of the tool can thus lead to serious injuries to the user (tackers or nail drivers can fire up to another ten shots).
This effect can be prevented by using the inline pressure regulators, which have a preset pressure determined by the application, thereby achieving energy efficiency and economy.

Artikkel

Märgistus	Keere	Eelseadistatud tööröhk	Läbivool	A (mm)	SW (mm)
K- 07 25 02 97	G 1/4	2 bar	600 - 800 l/min	66,6	16
K- 07 25 02 98	G 1/4	3 bar	600 - 800 l/min	66,6	16
K- 07 25 02 99	G 1/4	4 bar	600 - 800 l/min	66,6	16
K- 07 25 03 00	G 1/4	5 bar	600 - 800 l/min	66,6	16
K- 07 25 03 01	G 1/4	6 bar	600 - 800 l/min	66,6	16
K- 07 25 03 02	G 1/4	8 bar	600 - 800 l/min	66,6	16

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.