


# K-W90 SVB

## Bulkhead elbow couplings

**HANSA FLEX**

### Omadused

|                     |   |
|---------------------|---|
| <b>Töörõhk</b>      | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C) |
| <b>Kruviühendus</b> | Polyamide (PA)  |
| <b>Klemmrõngas</b>  | Polypropylene (PP)  |
| <b>Mutter</b>       | Polypropylene (PP)  |



### Vihje

Lisaandmed saate soovi korral.

### Kirjeldus

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. <br>Not suitable for use with acids.

### Artikkel

| Märgistus      | Keere      | Vooliku jaoks | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|------------|---------------|------------|------------|-------|
| K- 07 40 32 78 | M 10 x 1   | 4 mm / 6 mm   | 43,0       | 25,0       | 14 mm |
| K- 07 40 32 79 | M 14 x 1,5 | 6 mm / 8 mm   | 53,0       | 33,0       | 19 mm |
| K- 07 40 32 80 | M 16 x 1,5 | 8 mm / 10 mm  | 58,0       | 36,0       | 22 mm |
| K- 07 40 32 81 | M 18 x 1,5 | 9 mm / 12 mm  | 67,0       | 43,0       | 24 mm |