


# K-VLST 2 X IG MS NI

Extensions, 2 x female thread, parallel - nickel-plated brass

**HANSA FLEX**

## Omadused

|                |                    |
|----------------|--------------------|
| Töötemperatuur | Max. 150 °C        |
| Surve          | Max. 60 bar        |
| Materjal       | Nikeldatud messing |



## Vihje

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Lisaandmed saate soovi korral.

## Kirjeldus

Suitable for air, water, oil, steam, etc.

## Lisateave

Further types and dimensions on request.

## Artikkel

| Märgistus      | Keere 1 | Keere 2 | L1<br>(mm) | SW    |
|----------------|---------|---------|------------|-------|
| K- 07 40 39 09 | M 5     | G 1/8   | 13,5       | 14 mm |
| K- 07 40 39 10 | G 1/8   | G 1/4   | 21,5       | 17 mm |
| K- 07 40 39 11 | G 1/8   | G 3/8   | 23,5       | 22 mm |
| K- 07 40 39 12 | G 1/4   | G 3/8   | 25,5       | 22 mm |
| K- 07 40 39 13 | G 1/4   | G 1/2   | 28,5       | 24 mm |
| K- 07 40 39 14 | G 3/8   | G 1/2   | 29,5       | 24 mm |
| K- 07 40 39 15 | G 1/2   | G 3/4   | 30,0       | 32 mm |
| K- 07 40 43 91 | G 1/2   | G 1/8   | 24,0       | 24 mm |
| K- 07 40 43 92 | G 1     | G 3/4   | 25,0       | 38 mm |