
K-PROP VENTIL LU GA 24 V DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Omadused					
Temperatuuri ulatus	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)				
Vahendid	Air, neutral gases, water, oil				
Rõhuvahemik	Vacuum (max. 8 bar)				
Juhtimine	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA				
Käitumine Failsafe'i puhul	Tight closure in case of loss of voltage				
Korpus, klapipesa	Brass				
Sisedetail	Stainless steel				
Ventiilitaldrik	FKM				
Tihendusmaterjal	FKM				





Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital.

Proportional valves allow the medium to be varied as a function of an electronic input variable.

br>By linking these valves to the electronics, it is possible to improve their accuracy and broaden their range of applications. A pressure regulator, for instance, needs to be suitable for several pressure ranges without having to adjust the pressure manually.

br>Proportional valves control the output pressure in a closed control loop proportionally to the selected setpoint signal. This output pressure, in other words, is continually compared with the specified setpoint and automatically adjusted according to actual parameter values.

Lisateave

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Märgistus	Ühendus	DN	max töörõhkude erinevus	Α	В	С
			(bar)	(mm)		(mm)
K- 07 25 09 91	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 92	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 93	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 94	G 3/8	7	1	85,0	48,0 mm	97,0

13.11.2025 HANSA-FLEX AG www.hansa-flex.com