

K-FLASCHENDRUCKR 200 N GASE

Pudeli rõhuregulaator, pudeli rõhk 200 bar, mittepõlevatele gaasidele


HANSA FLEX

Omadused

Sisu manomeeter 0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene

Materjal Pressitud messing

Äärikühendus Nut 3/4



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Artikkel

Märgistus	Gaasi liik	Töörõhk bar
K- 07 25 07 11	Oxygen	0 - 10,0 bar
K- 07 25 07 12	Oxygen	0 - 20,0 bar
K- 07 25 07 14	Compressed air	0 - 10,0 bar
K- 07 25 07 15	Compressed air	0 - 20,0 bar
K- 07 25 07 16	Nitrogen	0 - 10,0 bar
K- 07 25 07 17	Nitrogen	0 - 20,0 bar
K- 07 25 07 18	Carbon dioxide	0 - 10,0 bar
K- 07 25 07 19	Carbon dioxide	0 - 20,0 bar
K- 07 25 07 20	Argon/helium	0 - 10,0 bar

Varuosad

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	Kaitsekorgid