

K-FLASCHENDRUCKR 200 GASE

Pudeli rõhuregulaator, pudeli rõhk 200 bar, põlevatele gaasidele


HANSA FLEX

Omadused

Sisu manomeeter 0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene

Materjal Pressitud messing

Äärikühendus Yoke



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Artikkel

| Märgistus | Gaasi liik | Töörõhk bar |
|----------------|--------------------------------------------------|--------------|
| K- 07 25 07 13 | Acetylene | 0 - 1,5 bar |
| K- 07 25 07 21 | Hydrogen, methane, illuminating gas, natural gas | 0 - 10,0 bar |

Varuosad

| | |
|-------------------------|-----------------------------|
| K-MANO SCHWEISSTECHNIK | Content pressure gauge |
| K-MANO SCHW | Pressure gauges for welding |
| K-SCHUTZKAPPE MANOMETER | Kaitsekorgid |