

K-BEFUELLVENTIL HANSA

Filling valves (start-up valves)

HANSA FLEX

Omadused

| | |
|-----------------------------|-------------------------------------------------|
| Sisendrõhk | 2.5 - 16 bar |
| Temperatuuri ulatus | -10 °C to +50 °C |
| Vahendid | Suruõhk |
| Ühenduskeere | Material: Die-cast zinc |
| Korpus | Material: Grivory® (PA 66) |
| Läbivoolu väärtuse mõõtmine | At P2 = 6 bar, pressure drop $\Delta p = 1$ bar |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. These valves prevent a sudden build-up of pressure accompanied by dangerous, jerky cylinder movements. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

Lisateave

See 3/2-way valves and filling units

See 3/2-way valves and filling units

Artikkel

| Märgistus | Keere | Läbivool (L/min) | A (mm) | B | C (mm) | D (mm) |
|----------------|-------|------------------|--------|----------|--------|--------|
| K- 07 25 11 11 | G 1/4 | 1300 | 52,0 | 78,0 mm | 45,0 | 33,0 |
| K- 07 25 11 12 | G 3/8 | 1300 | 52,0 | 78,0 mm | 45,0 | 33,0 |
| K- 07 25 11 13 | G 3/8 | 3400 | 63,0 | 111,5 mm | 53,5 | 58,0 |
| K- 07 25 11 14 | G 1/2 | 3400 | 63,0 | 111,5 mm | 53,5 | 58,0 |
| K- 07 25 11 15 | G 3/4 | 8750 | 85,0 | 112,0 mm | 58,0 | 54,0 |
| K- 07 25 11 16 | G 1 | 8750 | 85,0 | 112,0 mm | 58,0 | 54,0 |

Varuosad

K-HALTERBAUSATZ HANSA Holder HANSA