


# K-NEBELOELER PC-BEHÄLTER STANDARD-MINI

Oil-mist lubricators with polycarbonate bowl

**HANSA FLEX**

## Omadused

<b>Sisendrõhk</b>	Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
<b>Aine temperatuur</b>	max. 60 °C
<b>Keskonnatemperatuur</b>	Max. 60 °C
<b>Läbivool</b>	650 l/min
<b>Tihendusmaterjal</b>	NBR
<b>Korpus</b>	Die-cast zinc, painted silver
<b>Tilgapüüdur</b>	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
<b>Õlisort</b>	CL 32 acc. to DIN 51517 - ISO VG 32
<b>Läbivoolu väärtuse mõõtmine</b>	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
<b>Muud andmed</b>	User manual on request



## Kirjeldus

Proportional lubricators in compact design, oil can be filled under pressure.

## Artikkel

Märgistus	Keere	A (mm)	B	C (mm)	D (mm)	DN
K- 07 25 08 83	G 1/8	40,0	144,5 mm	49,5	95,0	5
K- 07 25 08 85	G 1/4	40,0	144,5 mm	49,5	95,0	5

## Varuosad

<b>K-ERSATZBEHÄLTER MULTI MINI</b>	Spare tank »multifix-mini« & »standard-mini«
<b>K-TROPFAUFSATZ POLYCARBO</b>	Drip attachment polycarbonate
<b>K-TROPFAUFSATZ METALL</b>	Drip attachment metal
<b>K-LOESBARE DOPPELNIPPEL MS</b>	Double nipples
<b>K-XV AGM MS NI</b>	Double nipples, parallel male thread, nickel-plated brass